

Technical sheet :

100 SEC S3




Capacities		Metric
Working height maximum (indoor)	h21	9.96 m
Working height maximum (outdoor)	h21	7.79 m
Platform height maximum (indoor)	h7	7.96 m
Platform height maximum (outdoor)	h7	5.79 m
Platform capacity	Q	227 kg
Lift capacity - Extension deck		113 kg
Number of people (inside / outside)		2 / 1
Weight and dimensions		
Platform weight*		2145 kg
Platform dimensions (length x width)	lp / ep	2.27 m x 0.81 m
Platform dimensions with extension (length)		3.18 m
Overall width	b1	0.81 m
Overall length	l1	2.44 m
Overall height	h17	2.32 m
Overall length (stowed)	l9	2.44 m
Overall height (stowed)	h18	1.94 m
External turning radius	Wa3	2.13 m
Ground clearance	m4	0.12 m
Ground clearance with pothole guards deployed	m6	0.02 m
Ground clearance with pothole guards folded	m2	0.12 m
Wheelbase	y	1.85 m
Performances		
Drive speed - stowed		3.20 km/h
Drive speed - raised		0.80 km/h
Raise speed / Lower speed		44 s / 33 s
Gradeability		25 %
Permissible leveling (front / side)		3 ° / 1.50 °
Wheels		
Tyres type		Non marking
Dimensions of front wheels / rear wheels		0,38x0,13m - 0,38x0,13m
Drive wheels (front / rear)		2 / 0
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		2 / 2
Engine/Battery		
Battery / Batteries capacity		6 V / 225 Ah
Integrated charger (V / A)		24 V / 27 A
Miscellaneous		
Ground Pressure		8.78 dan/cm2
Hydraulic tank capacity		17 l
Noise to environment (LwA)		< 70 dB
Vibration on hands/arms		< 2.50 m/s²
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)


*Varies according to options and standards of the country to which the machine is delivered

100 SEC S3 - Load chart

Load Chart metric



100 SEC S3 - Dimensional drawing



Equipment

Standard

2 swing out component trays
220V predisposition in the platform
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
Battery charge indicator lamp
CAN bus technology
Descent alarm
Dynamic hydraulic braking on front wheels
Emergency stop
Folding rails with half height swing gate
Horn in the platform
Hour meter
Integrated diagnostic assistance
Load management according to environment (indoor/outdoor)
Manual emergency lowering
Multi-voltage integrated charger
Non-marking rubber tyres
Pothole protection with automatic operation
Rear wheel multiple disc brakes
Side and rear forklift pockets

Optional

Beep on every movement
Biodegradable oil
Cold weather protection oil
Safety harness



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes